

SUPRA BAND



UNIVERSAL DOUBLE-SIDED BUTYL TAPE WITH HIGH ADHESIVENESS

PEERLESS

Water and air resistant, it guarantees adhesion even to wet supports and at low temperatures.

ELASTIC

Also suitable for sealing wood-wood joints (it compensates for the natural movements of the material).

COMPOSITION

release liner
silicone coated paper

glue
double-sided grey butyl compound



TECHNICAL DATA

Properties	standard	value	USC conversion
Ageing resistance	-	long duration	-
Initial Tack	ASTM D 2979	6 N	1.35 lbf
Adhesion on steel at 180°	ASTM D 1000	16 N/cm	9.14 lbf/in
Adhesiveness on concrete 180°	-	32 N/cm	18.27 lbf/in
Vertical sliding	ISO 7390	absent	-
Temperature resistance	-	-30 / +90 °C	-22 / 194 °F
Application temperature	-	-5 / +40 °C	+23 / 104 °F
Storage temperature ⁽¹⁾	-	+5 / +40 °C	+41 / 104 °F
Solvents	-	no	-
VOC emissions	ISO 16000	30 µg/m ³	-
French VOC classification	ISO 16000	A+	-

⁽¹⁾Store the product in a cool, dry place for no more than 12 months.
Waste classification (2014/955/EU): 08 04 10.

CODES AND DIMENSIONS

CODE	B	s	L	B	s	L	
	[mm]	[mm]	[m]	[in]	[mil]	[ft]	
SUPRA6	6	4	6	0.2	160	20	16
SUPRA10	10	4	6	0.4	160	20	22

■ FIELDS OF APPLICATION



■ RELATED PRODUCTS



DOUBLE BAND
page 62



OUTSIDE GLUE
page 154



SUPERB GLUE
page 150



SPECIAL BUTYL MIX

The modified butyl formulation of the product allows instant and permanent adhesion to all building materials. In addition, the material is impermeable to water and steam, ensuring a perfect seal.

FAST INSTALLATION

Its adhesive power also allows the sealing of damp or porous surfaces without the need to apply additional products, saving time and money.