

START BAND

WATERPROOFING PROFILE WITH HIGH MECHANICAL RESISTANCE

ELASTICITY

Thanks to its elasticity, it is extremely easy to install even around corners and it is resistant to perforations or mechanical fastening.

DURABILITY

It is compatible with bitumen, it does not degrade and it is UV-resistant. It is resistant to walking wear and cold temperatures.



COMPOSITION


support
EPDM-based synthetic rubber

TECHNICAL DATA

Properties	standard	value	USC conversion
Tensile strength	DIN 53504	≥ 6,5 MPa	-
Resistance to tearing	DIN 53504	≥ 25 kN/m	≥ 2.86 lbf/in
Elongation	DIN 53504	≥ 300%	-
Dimensional tolerance	DIN 7715-5	conforming (class P3)	-
Reaction to fire	EN 13501-1	class E	-
Resistance to UV and resistance to ozone	DIN 7864-1	conforming	-
Water vapour resistance factor (μ)	EN 1931	32000	128 MN·s/g
Temperature resistance	-	-30 / +100 °C	-22 / +212 °F

⁽¹⁾Store the product in a dry, covered location.
Waste classification (2014/955/EU): 17 02 03.

CODES AND DIMENSIONS

CODE	B	s	L	B	s	L		
	[mm]	[mm]	[m]	[in]	[mil]	[ft]		
1	START100	100	0,8	25	3.9	32	82	6
	START150	150	0,8	25	5.9	32	82	4
	START200	200	0,8	25	7.9	32	82	3
	START250	250	0,8	25	9.8	32	82	2
2	STARTA120	120	0,6	20	4.7	24	66	6
	STARTA160	160	0,6	20	6.3	24	66	6

■ FIELDS OF APPLICATION



■ RELATED PRODUCTS



CUTTER
page 328



PRIMER SPRAY
page 102



HAMMER STAPLER 22
page 330



WIDE RANGE, INCLUDING ADHESIVE

Also available in an adhesive version (STAR-TA120 and STARTA160), ideal when applied in combination with ALU START, for an infallible connection to the ground.

SAFETY

It protects walls and foundation walls against rising damp over time, even at extreme temperatures. Also suitable as a general sealing wall barrier.